INNOVATIVE PRODUCERS CHOOSE SURESTRIKE

Surestrike SS150

SUPERIOR OUTPUT PROCESS FLEXIBILITY
REMARKABLE ECONOMICS

- *Fewer moving parts with in-field maintenance and rebuild capabilities*
- *Double acting hydraulic system with low cost operation*
- *One of the largest striker pins in the industry providing long life and low-cost operation*
- *Heat treated - stress relieved frame assembly*
- *Heavy duty "pin style" adaptor bracket for stronger frame design*
- *Heavy duty durable urethane buffers for increased protection*

Single Blow Impact Energy - Ft. Lbs	*150,000*
Blow Per Minute	*15*
Approximate Operating Weight - Lbs	*30,000*
Operating Pressure Range - PSI	*4000-5000*
Hydraulic Flow Range - GPM	*45-60*
Striker Pin Diameter - inches	*11*
Standard Striker Pin Length - inches	*42*
Excavator Class - Stick Mount - Lbs	*175,000*
Excavator Class - Boom Mount - Lbs	*125,000*
Loader Class - Yards	*10-11*

These specifications are representative only.
For detailed specifications contact your local distributor or Surestrike.

MADE IN USA

www.surestrikeinternational.com
Call +1 715-472-8844

SURESTRIKE