INNOVATIVE PRODUCERS CHOOSE SURESTRIKE

Surestrike SS50

SUPERIOR OUTPUT PROCESS FLEXIBILITY
REMARKABLE ECONOMICS

- *Fewer moving parts with in-field maintenance and rebuild capabilities*
- *Double acting hydraulic system with low cost operation*
- *One of the largest striker pins in the industry providing long life and low-cost operation*
- *Heat treated - stress relieved frame assembly*
- *Heavy duty "pin style" adaptor bracket for stronger frame design*
- *Heavy duty durable urethane buffers for increased protection*

Single Blow Impact Energy - Ft. Lbs	*50,000*
Blow Per Minute	*15*
Approximate Operating Weight - Lbs	*18,500*
Operating Pressure Range - PSI	*2700-3200*
Hydraulic Flow Range - GPM	*35-50*
Striker Pin Diameter - inches	*8*
Standard Striker Pin Length - inches	*33*
Excavator Class - Stick Mount - Lbs	*100,000*
Excavator Class - Boom Mount - Lbs	*70,000*
Loader Class - Yards	*5-6*

These specifications are representative only.
For detailed specifications contact your local distributor or Surestrike.

MADE IN USA

www.surestrikeinternational.com
Call +1 715-472-8844

SURESTRIKE